



is the finest in the industry. It turns passersby into an audience, and a building into a billboard – a vivid, multi-colored multi-messaging platform with endless revenue generating possibilities. BROADCAST custom printing leads the industry with the following features:

#### Full Color:

A full range of vivid colors.

#### Maximum-size:

The largest printing area available.

#### Alternating Messages & Images:

Select multiple messages for your building wrap.

#### Flexible Order Size:

Orders as small as eight rolls, and as large as needed.

Visit our WRAPLAB™ at  
[prolinx.customprintwrap.com](http://prolinx.customprintwrap.com)

Call our experts at **(800) 552-7775** to find out how customer printing can expand your business!



## Typical Physical Properties

Property	Standard	UoM	Typical Result <sup>1</sup>
Basis Weight	ASTM D 5261	g/m <sup>2</sup>	65
Breaking Strength (MD/CD)	ASTM D 882	lbs/inch	46/36
Water Vapor Transmission Rate	ASTM E 96, Method A	g/m <sup>2</sup> /24 hours	70
Water Vapor Permeance	ASTM E 96, Method A	perms	10
Water Resistance	ASTM D 779	minutes	60
Air Resistance	TAPPI T 460	sec/100 cc	14
Flame Spread Index	ASTM E 84	Class	A
Smoke Developed Index	ASTM E 84	Class	A
Ultraviolet Light (UV) Exposure	Internal	Days	300

Test data is based on average results and is not limiting specifications. Normal manufacturing variation may produce results above or below typical data and should not be considered or interpreted as minimum or maximum values.

#### WARRANTY INFORMATION

A ten- (10-) year limited warranty applies to PROLinx® Select building wrap. To obtain a copy of this warranty, please visit [BlueLinxCo.com](http://BlueLinxCo.com) or call **888-502-BLUE**. No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

#### PRECAUTIONS

**Warning:** Protect from high heat or other ignition sources during shipment, storage and application.

#### STORAGE

Take care to protect PROLinx building wrap from exposure to direct sunlight during storage. It is recommended that building wrap to be stored inside or under cover.

#### ROLL SIZES\*

3' x 100'	3' x 150'	4.5' x 100'	4.5' x 150'
5' x 100'	5' x 150'	9' x 100'	9' x 150'
9' x 195'	10' x 100'	10' x 150'	10' x 195'

\*Not all rolls available for BROADCAST custom printing, ask your sales representative for more details.

Select



Professional contractor grade  
for moderate to severe weather

PROLinx®  
BUILDING WRAP

Select



# YOUR BARRIER OF PROTECTION AGAINST THE ELEMENTS.

**PROLinx**  
BUILDING WRAP  
**Select**

PROLinx BUILDING WRAP	<b>Select</b>	<b>Drain</b>	<b>Plus LP</b>	<b>Plus HP</b>
Meets Building Code	•	•	•	•
Energy Efficient	•	•	•	•
Optimal UV Resistance	•	•	•	•
Superior Tear Strength	•	•	•	•
BROADCAST™ Custom Printing	•	•	•	•
Enhanced Multi-Directional Drainage Plane		•		
Certified Air Barrier			•	•
More Robust Water Resistance			•	•



PROLinx® Select is the best weather barrier available for projects requiring standard weather protection. Woven fabric construction provides exceptional strength and durability at a low weight. Balanced breathability and reliable water-resistance combine to make PROLinx Select the best value in commercial-grade weather protection. PROLinx Select is also UV-stable to resist degradation for up to 300 days when exposed to the elements.

PROLinx Select is available with BROADCAST® custom printed advertising. Now you can custom print PROLinx Select in full color with alternating messages in the industry's smallest minimum quantities.

**Strong & Durable:** PROLinx Select is cross-woven to resist tearing around fasteners and will endure tough jobsite conditions during installation.

**Moisture Protection:** PROLinx Select is water-resistant and provides reliable protection in finished wall assemblies.

**Breathable:** PROLinx Select is designed to help moisture vapor easily escape the wall assembly.

**Stable:** PROLinx Select is treated to resist excessive degradation from normal UV exposure for up to 300 days. It can be left exposed for two to three times longer than comparable competitor products.

**Simple Application:** Lightweight yet durable, PROLinx Select is translucent which makes locating studs, openings, and corners quick and easy.

**Meets Building Codes:** PROLinx Select is rated for commercial projects. It meets or exceeds applicable building codes for weather resistant barriers and creates a healthy, energy-efficient building.

Broadcast and WrapLab are trademarks of Jumpstart Consultants, Inc. International patents pending for the WrapLab custom print application. .

**1-888-502-BLUE | [www.BlueLinxCo.com](http://www.BlueLinxCo.com)**

**BlueLinx**  
America's Building Products Distributor